

EG-X SERIES

“xcellance our best”



- All steel 4"x 6" one piece welded frame
- Heavy duty gantry
- Unit is a true dual drive
- 5hp high frequency spindle
- High performance industrial application
- Ac servo and drives
- Industrial motion controller,
- 3000 ipm positioning speed
- Linear rails all axis
- Rack and pinion drive system on x and y axes
- Industrial anti backlash control system
- Ball screw drive on z axis
- Mdf tabletop
- Automatic z height touch top
- Repeatability +/- .001
- Resolution .0004
- Spindle boot for a dust collection
- Full 3D files processing capability
- Control panel mounted to table frame
- Clamp, collet and wrench
- Easy access emergency stop
- Operational manual
- 240vac- 3phase unit

starting at:
\$48,995.

WHATS INCLUDED

Everything to begin high-level production—industrial motion control software, spindle, four stepper motors and drives, complete control cabinet, and, of course, the CNC machine.

All you have to do is supply power.

SUPPORT

Our experienced team is always ready to help. To keep downtime to a minimum, we can log in remotely to diagnose any problems. And most parts orders can reach you the next day.

The EG-X means business.

Give your company the greatest edge with the industrial-grade EG-X series, the best CNC machine available for high-production needs. All EG-X machines use a double-steel gantry, steel sideplates with an aluminum tranny system, one-piece steel-welded frame, HiWin linear rails and bearings on all axes, and a HiWin ball screw assembly on the z-axis.

Contact Info:

Eagle Eye CNC
13555 Back Valley Road
Sale Creek, TN 37373

ph: 423-228-2349
fax: 423-228-2346

email: sales@eagleeyecnc.com
website: www.eagleeyecnc.com
youtube: www.youtube.com/eagleeyecnc

EG-X SERIES GENERAL SPECIFICATION

Model number	203	404	408	410	508	510
Cutting area	24 x 36	48 x 48	48 x 96	48 x 120	60 x 96	60 x 120
Z axis clearance	8	8	8	8	8	8
Z axis travel	8	8	8	8	8	8
Overall length	72	84	135	160	130	160
Overall width	38	62	62	62	74	74
Overall height	72	72	72	72	72	72
Weight	1250	1575	1950	2150	2175	2400

